IN THE CLAIMS:

Please amend the Claims 1~6 as follows:

1. (currently amended) A folding and portable electric scooter comprising a body member, a cover member, a seat frame and two handles respectively secured to two handle bars, wherein ~~interior of~~ the body member ~~is installed~~ has an interior and a transmission device comprising an electric motor, a battery and a belt installed in said interior in said body member; a front wheel and a rear wheel ~~are pivot~~ pivotally jointed to a front and a rear ~~end~~ portion of the body member respectively, and a foot stand ~~is~~ fixedly positioned to a side of the body member; and wherein the electric motor drives the belt, and the belt ~~wraps round~~ is wound on a hub at a side of the rear wheel; ~~and is characterized in that~~: the improvement which comprises:

the cover member ~~is pivot~~ pivotally jointed to a wheel frame of the front wheel, and the two handles ~~are~~ configured on a ~~moveable~~ movable end of the cover member; ~~an~~ a reverse U-shaped bracket ~~is~~ bolted ~~onto~~ into the cover member, and ~~an~~ a reverse U-shaped fastening bracket ~~is~~ configured atop the reverse U-shaped bracket; ~~each end of~~ the fastening bracket ~~is~~ downwardly bent to ~~respectively~~ form a pair of neck members, ~~and~~ having each said neck member formed with a fastening hook thereon ~~is respectively configured on each of the necks thereof~~, two fastening holes defined in said two handle bars ~~provide~~ for respectively engaging the fastening hooks of the fastening bracket ~~to hook and fasten position thereinto~~; a recess hole ~~is~~

defined ~~on~~ in each ~~of two ends~~ end atop the fastening bracket, and a fixing bolt ~~is~~ bolted into each ~~of the~~ said recess ~~holes~~ hole, ~~moreover, the fastening bracket utilizes~~ whereby upon altering of the position of the fixing bolts ~~to alter position~~ within the recess holes, ~~and thereby facilitate fastening down or loosening of the handles~~ the handle bars can be fastened or loosened for unfolding or folding the electric scooter; and upon folding of the electric scooter ~~being folded away~~, the cover member completely covers the body member, and ~~when~~ upon unfolding of the electric scooter ~~is in usage~~ for use, the cover member functions as a front frame for the electric scooter;

a seat ~~is~~ installed atop the seat frame configured at a ~~tail end~~ rear portion of the body member, and wherein the seat frame can be folded away into the body member; a ~~bar is~~ pair of bars respectively bolted to ~~each of~~ two front sides of the seat frame, and a pair of movable ~~strip is~~ strips each configured in an interior of each ~~of the bars~~ said bar, a holding bar ~~is configured between and joins extremities of~~ joining the two ~~moveable~~ movable strips; a ~~hook eye is respectively~~ notch defined in each ~~of the bars~~ said bar and ~~provide for~~ two inclined wedge pieces each engaged with each said notch ~~to respectively fasten thereinto~~; a spring ~~is~~ connected to an underside of each of the wedge ~~pieces~~ piece; whereby upon downward pushing ~~down on~~ of the holding bar ~~thereby enables~~ to enable the ~~moveable~~ movable strips to outwardly push the wedge pieces~~, and thus separate~~ to disengage the wedge pieces from ~~being fastened in~~

~~the hook eyes~~ the notches, ~~whereupon~~ the seat frame can be folded ~~down,.~~ ~~if the seat frame is lightly pulled back to an upright position, a fastening is utilized to fix position and thereby enable formation of a seat.~~

2. (currently amended) The folding and portable electric scooter in accordance with claim 1, wherein a foldaway carry handle is configured on top of the cover member, a headlight ~~is~~ configured at a side of the carry handle; a power switch and a battery charge switch cover ~~are~~ configured on a side face of the cover member, and a folding panel ~~is~~ configured on a frontal section at a tail end of the cover member.

3. (currently amended) The folding and portable electric scooter in accordance with claim 1, wherein a brake device is bolted to the handle, and the brake device is connected to a braking system by means of a brake cable.

4. (currently amended) The folding and portable electric scooter in accordance with claim 1, wherein a ~~loose~~ movable pull-bar is configured on a back of the cover member~~, and upwardly pulling on the loose pull-bar tugs on~~ operatively tugging two pull cables, ~~whereupon~~ the two pull cables respectively ~~actuate~~ operatively actuating two fastening hooks to respectively disengage ~~fastening from~~ a locating hole of the wheel frame of the front wheel of the cover member and to disengage a fastening edge of a rear wheel frame of the body member~~, thereby~~ for opening up the electric scooter~~;.~~ ~~when folding away the electric scooter, pulling up on the loose pull-bar tugs the two pull cables, and~~

~~actuates the fastening hook to disengage fastening from the locating hole, thereby enabling folding away of the front frame.~~

5. (currently amended) The folding and portable electric scooter in accordance with claim 1, wherein two auxiliary wheels are configured on a frontal section of the front wheel of the body member, and a pull rod is configured on a frontal section of the cover member~~,~~. u~~pon folding away, pulling on the pull rod thereby enables the electric scooter to be pulled along ground by means of the auxiliary wheels.~~

6. (currently amended) The folding and portable electric scooter in accordance with claim 1, wherein a brake light is configured at a rear portion of the seat installed atop the seat frame.